## **LAMBORGHINI R R 503, DT, S, DTS** (1975-1984)



| ENGINE 1003/3<br>Capacity: 6,6 liter |                          |          |
|--------------------------------------|--------------------------|----------|
| USE                                  |                          | CLIMATE  |
| Normal                               |                          | Tropical |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 |          |
| Multifleet SCD 40                    | HDX 40                   |          |

Check every 10 hours, change every 125 hours

| USE                      | CLIMATE       |
|--------------------------|---------------|
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| HDX 30                   |               |

Check every 10 hours, change every 125 hours

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Multifleet SHPD 15W-40   | HDX 20W-20               |          |

Check every 10 hours, change every 125 hours

|                          | CLIMATE                  |
|--------------------------|--------------------------|
|                          | Moderate                 |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30     | Agrifluid HT             |
|                          |                          |

Check every 125 hours, change every 1000 hours

| HUB REDUCTIONS FRONT Capacity: 1 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE                                    |                          | CLIMATE                  |
| Normal                                 |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra              | Kroontrak MTH 10W-30     | Agrifluid HT             |
| Check every 125 hours, change every    | 1000 hours               |                          |

## **LAMBORGHINI R R 503, DT, S, DTS** (1975-1984)



| HUB REDUCTIONS REAR Capacity: 2 liter |                          |                          |
|---------------------------------------|--------------------------|--------------------------|
| USE                                   |                          | CLIMATE                  |
| Normal                                |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra             | Kroontrak MTH 10W-30     | Agrifluid HT             |

Check every 125 hours, change every 1000 hours

| TRANSAXLE/HYDRAULIC SYSTEM Capacity: 24 liter | 12/3                     |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra                     | Kroontrak MTH 10W-30     | Agrifluid HT             |

Check every 125 hours, change every 3000 hours

| POWER STEERING<br>Capacity: 2 liter |                          |                          |
|-------------------------------------|--------------------------|--------------------------|
| USE                                 |                          | CLIMATE                  |
| Normal                              |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| ATF Dexron II-D                     | Perlus Biosynth 46       | Perlus H 46              |
| Check every 125 hours, change ev    | ery 1000 hours           | '                        |

| GREASE POINTS/NIPPLES    |                          |          |
|--------------------------|--------------------------|----------|
| USE                      |                          | CLIMATE  |
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2  |          |

Check every 50 hours

| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT     |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 |          |
| Q7 MP Calcep Grease WR 2                       | Caliplex HD Grease EP 2  |          |
| Check every 250 hours, change every 1000 hours |                          |          |

## **LAMBORGHINI R R 503, DT, S, DTS** (1975-1984)



| STEERING BOX<br>Capacity: 1,5 liter |                          |                          |
|-------------------------------------|--------------------------|--------------------------|
| USE                                 |                          | CLIMATE                  |
| Normal                              |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra           | Kroontrak MTH 10W-30     | Agrifluid HT             |
| Check every 125 hours, change ever  | v 1000 hours             |                          |

Check every 125 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.