

# LAMBORGHINI R3 EVO COM 3 R3 EVO 110

## STAGE 3A->5001 (2009-2015)



**ENGINE** Deutz TCD 2012 L04 2V  
Capacity: 10 liter, Filter capacity: 1 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 2  
**Agridiesel MSP 15W-40**

PRODUCT RECOMMENDATION 3  
**Agridiesel CRD+ 15W-40**

*Check every 10 hours, change every 500 hours/ 12 months*

USE  
Biodiesel B100

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 2  
**Agridiesel MSP 15W-40**

PRODUCT RECOMMENDATION 3  
**Agridiesel CRD+ 15W-40**

*Check every 10 hours, change every 250 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 6 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT-Plus**

*Check every 250 hours, change every 1000 hours/ 24 months*

**HUB REDUCTIONS FRONT**  
Capacity: 1,5 liter (each)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT-Plus**

*Check every 250 hours, change every 1000 hours/ 24 months*

**POWER TAKE OFF FRONT**  
Capacity: 2,5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT-Plus**

*Check every 250 hours, change every 500 hours*

# LAMBORGHINI R3 EVO COM 3 R3 EVO 110

## STAGE 3A->5001 (2009-2015)



### TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING

Capacity: 52 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

Check every 50 hours, change every 1000 hours/ 24 months

### HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Change every 50 hours

### COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.