

LAMBORGHINI R3 T-TB COM3 R3 85 T - >1001 (2010-2015)



ENGINE Deutz TCD 2012 L04 2V C3 MT62
Capacity: 10 liter, Filter capacity: 1 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	---	--

Check every 10 hours, change every 500 hours/ 12 months

USE Biodiesel B100		CLIMATE Moderate
------------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	---	--

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT

Capacity: 6 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 3 Agrifluid HT-Plus
--	---	---

Check every 250 hours, change every 1000 hours/ 24 months

HUB REDUCTIONS FRONT

Capacity: 1,5 liter (each hub)

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 3 Agrifluid HT-Plus
--	---	---

Check every 250 hours, change every 1000 hours/ 24 months

POWER TAKE OFF FRONT

Capacity: 2,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 3 Agrifluid HT-Plus
--	---	---

LAMBORGHINI R3 T-TB COM3 R3 85 T - >1001 (2010-2015)



TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 52 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 50 hours, change every 1000 hours/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.