LAMBORGHINI R4 R4.110 (2005-2009)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Armado Synth 5W-30	

Check every 10 hours, change every 300 hours/12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Armado Synth 5W-30	

Change every 50 hours

DIFFERENTIAL FRONT (4x4) Capacity: 10,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 300 hours, change every 1200 hours/ 12 months

_

Check every 300 hours, change every 1200 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Check every 300 hours, change every 1200 hours/ 12 mg	onths

Check every 300 hours, change every 1200 hours/ 12 months

LAMBORGHINI R4 R4.110 (2005-2009)



TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 71 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Check every 300 hours, change every 1200 hours/ 12 months	

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 50 hours	·

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	,	

COOLING SYSTEM Capacity: 12 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 10 hours, change every 1200 hours/ 12 mo	nths

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.