

# LAMBORGHINI R6 R6.135 HI-PROFILE DCR 4V STAGE 3A (2010-2015)



**MOTOR** Deutz TCD 2012 L04 4V DCR  
Kapacitet: 10 liter, Filterkapacitet: 1 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                              |                               |
|-----------------------------|------------------------------|-------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Biodiesel B100 | Moderat |

|                             |                              |                               |
|-----------------------------|------------------------------|-------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

**DIFFERENTIALE FOR**  
Kapacitet: 5,8 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |                           |
|-----------------------------|------------------------------------|---------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                | PRODUKTANBEFALING 3       |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube LS 80W-90</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

**KRAFTOVERFØRING FOR**  
Kapacitet: 0,9 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                  |                          |
|-----------------------------|----------------------------------|--------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

Kontroller alle 250 timer, skift alle 500 timer

**NAVREDUKTIONER BAG**  
Kapacitet: 9 liter (hvert nav)

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |                           |
|-----------------------------|------------------------------------|---------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                | PRODUKTANBEFALING 3       |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube LS 80W-90</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

# LAMBORGHINI R6 R6.135 HI-PROFILE DCR 4V STAGE 3A (2010-2015)



## NAVREDUKTIONER FOR

Kapacitet: 0,8 liter (hvert nav)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2  
**Unigear HS GL-3/GL-5 80W-90**

PRODUKTANBEFALING 3  
**Gearlube LS 80W-90**

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

## TRANSAKSEL/TRANSMISSION

Kapacitet: 80 liter (Ophængt bagaksel), Kapacitet: 78 liter (Stiv bagaksel)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Kroontrak CVT 10W-40**

PRODUKTANBEFALING 2  
**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 3  
**Agrifluid HT-Plus**

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**SP Matic 2032**

Skift alle 24 måneder

## SMØREPUNKTER/NIPLER

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Labora Grease**

PRODUKTANBEFALING 2  
**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3  
**MP Lithep Grease EP 2**

Skift alle 50 timer

## KØLESYSTEM

Kapacitet: 21 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Coolant SP 12 EVO**

Kontroller alle 10 timer, skift alle 1000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.