

LAMBORGHINI R6 R6.140 DCR STAGE 3A- >20001 (2010-2015)



MOTOR Deutz TCD 2012 L06 2V DCR
Kapacitet: 13 liter, Filterkapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Biodiesel B100	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR
Kapacitet: 5,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 0,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Kontroller alle 250 timer, skift alle 500 timer

NAVREDUKTIONER BAG
Kapacitet: 9 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

LAMBORGHINI R6 R6.140 DCR STAGE 3A- >20001 (2010-2015)



NAVREDUKTIONER FOR

Kapacitet: 0,8 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3
Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

TRANSAKSEL/TRANSMISSION

Kapacitet: 80 liter (Ophængt bagaksel), Kapacitet: 78 liter (Stiv bagaksel)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

PRODUKTANBEFALING 2
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3
Agrifluid HT-Plus

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Skift alle 24 måneder

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 12 EVO

Kontroller alle 10 timer, skift alle 1000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.