LAMBORGHINI RACING 150 RACING (1994-2001)



ENGINE Perkins 1000.6-ATI Capacity: 15 liter, Filter capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	
0k k	

Check every 10 hours, change every 150 hours/ 12 months

DIFFERENTIAL FRONT (4x4) Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Charle aver 150 hours aborre aver 120	2 hours / 12 months	

Check every 150 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Chack avant 125 hours, change avant 1200 hours (12 months		

Check every 125 hours, change every 1200 hours/ 12 months

POWER TAKE OFF Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 150 hours, change every 1200 hours

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 27/27 Capacity: 108 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check even (150 hours, change even (1200 hours) (12 months		

Check every 150 hours, change every 1200 hours/ 12 months

LAMBORGHINI RACING 150 RACING (1994-2001)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Chaok avant 200 hours, abanga avant 24 mantha		

Check every 300 hours, change every 24 months

Check every 50 hours

COOLING SYSTEM Capacity: 16 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -33 MPG		
Check every 10 hours, change every 2400 hours/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.