## **LAMBORGHINI REKORD COM3 REKORD 40E ->L10S403WX1E1001** (2008-2015)



<b>ENGINE</b> Perkins 1000.3-W3 Capacity: 7,7 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 300 hours

TRANSAXLE/HYDRAULIC SYSTEM Capacity: 35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 50 hours, change every 1200 hours/ 24 months		

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 50 hours		

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Change every 50 hours	1			

COOLING SYSTEM Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Check every 10 hours, change every 1200 hours/ 24 months		

PRODUCT RECOMMENDATION

## LAMBORGHINI REKORD COM3 REKORD 40E ->L10S403WX1E1001 (2008-2015)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.