

# LANDINI SERIES 7 ROBO-SIX 7-215 ROBO-SHIFT T4I / IIIB (2016-2021)



**ENGINE** FPT NEF 6.7-TA(A)  
Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 500 hours/ 6 months*

## DIFFERENTIAL FRONT

Capacity: 6 liter (Rigid axle), Capacity: 4 liter (Suspended front axle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 1000 hours/ 12 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 250 hours*

## HUB REDUCTIONS FRONT

Capacity: 1,5 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 1000 hours/ 12 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 250 hours*

# LANDINI SERIES 7 ROBO-SIX 7-215 ROBO-SHIFT T4I / IIIB (2016-2021)



## HUB REDUCTIONS REAR

Capacity: 11 liter (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Change every 18 months/ 1500 hours

## POWER TAKE OFF FRONT

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Kroontrak MTH 10W-30</b>

Change every 6 months/ 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Kroontrak MTH 10W-30</b>

Change every 250 hours

## TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 92 liter, Capacity: 104 liter (+ front hitch)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>	

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>	

Change every 500 hours

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

# LANDINI SERIES 7 ROBO-SIX 7-215 ROBO-SHIFT T4I / IIIB (2016-2021)



## COOLING SYSTEM

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 10 hours, change every 1000 hours/ 12 months*

## SELECTIVE CATALYST REDUCTION SYSTEM (SCR)

Capacity: 38 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*