

LAVERDA 3000 3350 AL (1983-1986)

ENGINE Fiat 8065 SI
Capacity: 13 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Check every 10 hours, change every 80 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 80 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Check every 10 hours, change every 80 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 80 hours

HUB REDUCTIONS FRONT

Capacity: 3,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 80 hours, change every 600 hours/ 12 months

TRANSAXLE MANUAL 3/3

Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 80 hours, change every 600 hours/ 12 months

LAVERDA 3000 3350 AL (1983-1986)**HYDRAULIC SYSTEM**

Capacity: 65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

*Check every 10 hours, change every 600 hours/ 12 months***HYDRAULIC SYSTEM HYDROSTATIC DRIVE**

Capacity: 85 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

*Check every 10 hours, change every 600 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

*Check every 10 hours***COOLING SYSTEM**

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Check every 10 hours, change every 600 hours/ 12 months***LEVELLING VESSEL(S)**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

LAVERDA 3000 3350 AL (1983-1986)**WOBBLE BOX**

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 80 hours, change every 600 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.