

LAVERDA 3000 3450 (1983-1986)



ENGINE Perkins 6.372.4
Capacity: 13 liter, Filter capacity: 0,5 liter

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 40	PRODUCT RECOMMENDATION 2 Multifleet SCD 30	
---	---	--

Check every 10 hours, change every 80 hours

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
--	--	--

Check every 10 hours, change every 80 hours

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
---	--	--

Check every 10 hours, change every 80 hours

USE Normal	CLIMATE Arctic
----------------------	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
--	--	--

Check every 10 hours, change every 80 hours

HUB REDUCTIONS FRONT

Capacity: 3 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 80 hours, change every 600 hours/ 12 months

TRANSAXLE MANUAL 3/3

Capacity: 10 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 80 hours, change every 600 hours/ 12 months

LAVERDA 3000 3450 (1983-1986)



HYDRAULIC SYSTEM Capacity: 20 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF-A		
<i>Check every 10 hours, change every 600 hours/ 12 months</i>		

HYDRAULIC SYSTEM HYDROSTATIC DRIVE Capacity: 65 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF-A		
<i>Check every 10 hours, change every 600 hours/ 12 months</i>		

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Check every 10 hours</i>		

COOLING SYSTEM Capacity: 24 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 10 hours, change every 600 hours/ 12 months</i>		

LEVELLING VESSEL(S) Capacity: 0,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

LAVERDA 3000 3450 (1983-1986)



WOBBLE BOX

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 80 hours, change every 600 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.