PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA BTI 220
(1998 AND AFTER)

ENGINE Perkins Capacity: 7,6 liter		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Multifleet SHPD 15W-40**		
Check every 300 hours, change every 900 hours		

DIFFERENTIAL FRONT Capacity: 8 liter		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid HT**		
Change every 900 hours		

DIFFERENTIAL REAR Capacity: 8 liter		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	**PRODUCT RECOMMENDATION 2** **Unigear HS GL-3/GL-5 80W-90**	
Change every 900 hours		

HUB REDUCTIONS FRONT Capacity: 1 liter		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	**PRODUCT RECOMMENDATION 2** **Unigear HS GL-3/GL-5 80W-90**	
Change every 900 hours		

HUB REDUCTIONS REAR Capacity: 1 liter		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	**PRODUCT RECOMMENDATION 2** **Unigear HS GL-3/GL-5 80W-90**	
Change every 900 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA BTI 220

(1998 AND AFTER)

TRANSFERBOX
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 900 hours

TRANSMISSION AUTOMATIC
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gear Oil Alcat 10W	**ATF Dexron II-D**	**ATF-A**

Change every 900 hours

TRANSMISSION/HYDRAULIC SYSTEM
Capacity: 110 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus AF 46**	

Change every 900 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 0,08 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
LHM +		

Check every 300 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 300 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MANITOU MANISCOPIC MT/MTA BTI 220
(1998 AND AFTER)

GREASE POINTS/NIPPLES TELESCOPIC BOOM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 300 hours

COOLING SYSTEM
Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367