

MANITOU MANISKOPISK MT/MTA TMT 322 (1998 OG EFTER)



MOTOR Perkins
Kapacitet: 5,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Skift alle 200 timer

GEAR/HYDRAULISK SYSTEM
Kapacitet: 35 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46

Skift alle 800 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 300 timer

SMØREPUNKTER/NIPLER TELESKOPISK ARM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Kontroller alle 300 timer

KØLESYSTEM
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 800 timer

MANITOU MANISKOPISK MT/MTA TMT 322 (1998 OG EFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.