Check every 10 hours, change every 150 hours

MASSEY FERGUSON 1200 MF 1250 (1994-2002)



ENGINE Capacity: 4,8 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
HDX 30		
Check every 10 hours, change every 150	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 20W-20		
Check every 10 hours, change every 150	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

DIFFERENTIAL FRONT (4x4) Capacity: 6,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Agrifluid HT	SP Gear 5015
Check every 50 hours, change eve	rv 300 hours	I

TRANSAXLE/HYDRAULIC SYSTEM 16/16 Capacity: 25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 50 hours, change ever	y 300 hours	'

MASSEY FERGUSON 1200 MF 1250 (1994-2002)



POWER STEERING Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 300 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours	1	

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	12 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.