

MASSEY FERGUSON 2000 MF 2725 (1985-1987)



ENGINE AT6.354.4C.C
Capacity: 17-19,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|-----------------------------|-----------------------------|
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Kroontrak CVT 10W-40 |

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 11-13 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 1000 hours

HUB REDUCTIONS FRONT (4x4)
Capacity: 3,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 1000 hours

POWER TAKE OFF FRONT
Capacity: 5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Kroontrak MTH 10W-30 | | |

Check every 100 hours, change every 1000 hours

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 16/12
Capacity: 88 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|-----------------------------|--|
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | |

Check every 100 hours, change every 1000 hours

MASSEY FERGUSON 2000 MF 2725 (1985-1987)**GREASE POINTS/NIPPLES OTHERS**

| USE | | CLIMATE |
|-----------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| <i>Check every 10 hours</i> | | |

GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE | | CLIMATE |
|------------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| <i>Check every 500 hours</i> | | |

COOLING SYSTEM

Capacity: 27 liter

| USE | | CLIMATE |
|--|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| <i>Check every 100 hours, change every 500 hours</i> | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.