MASSEY FERGUSON 30/40 MF 38 (1991-2000)



ENGINE Valmet 612DSL/DSJL Capacity: 23 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 200 h	nours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	Multifleet SCD 20W-20	
Check every 10 hours, change every 200 h	nours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 200 h	nours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 200 h	nours	
HUB REDUCTIONS FRONT Capacity: 12 liter		

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 100 hours, change every 500 hours/24 months

TRANSAXLE MANUAL 3/3 Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 100 hours, change every 500 hours/24 months

MASSEY FERGUSON 30/40 MF 38 (1991-2000)



HYDRAULIC SYSTEM Capacity: 43 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus AF 100		
Check every 50 hours, change every 1000	hours/ 36 months	

01 1 501 1 1000	1 (00 //	
Perlus H 68	Perlus AF 68	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 50 hours, change every 1000 hours/ 36 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 32 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 50 hours, change every	/ 24 months	1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.