PRODUCT RECOMMENDATION

MASSEY FERGUSON 300 MF 362 (1990-1994)

ENGINE A4.236
Capacity: 6,8 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		

Check every 10 hours, change every 250 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SHPD 10W-40	**HDX 30**	

Check every 10 hours, change every 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 250 hours, change every 1000 hours/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MASSEY FERGUSON 300 MF 362 (1990-1994)

TRANSAXLE/HYDRAULIC SYSTEM 8/2
Capacity: 43,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 100 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 250 hours, change every 2000 hours/ 12 months

POWER STEERING
Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 100 hours

GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 500 hours

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 100 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MASSEY FERGUSON 300 MF 362 (1990-1994)

GREASE POINTS/NIPPLES SLIDING JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 500 hours

COOLING SYSTEM
Capacity: 14,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant -38 Organic NF	**Coolant -26**	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367