

MASSEY FERGUSON 6100 MF 6120 (1995-1996)



ENGINE Perkins 4.41
Capacity: 7,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 3

Kroontrak CVT 10W-40

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT (4x4)
Capacity: 6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM 16/16
Capacity: 62 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

Check every 100 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Check every 10 hours

MASSEY FERGUSON 6100 MF 6120 (1995-1996)

**COOLING SYSTEM**

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 100 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.