

MASSEY FERGUSON 6400 6485 (2004-2007)

ENGINE Sisu 66ETA
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT

Capacity: 6 liter, Capacity: 11-12 liter (Dana), Capacity: 8,5 liter (Suspended front axle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

HUB REDUCTIONS FRONT

Capacity: 2 liter (Dana), Capacity: 1,3 liter (Suspended front axle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

TRANSAXLE/HYDRAULIC SYSTEM 12/12

Capacity: 109 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		

Check every 10 hours, change every 1200 hours

MASSEY FERGUSON 6400 6485 (2004-2007)**GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1 Multi Purpose Grease 3		
---	--	--

Check every 50 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2
--	---	--

Check every 50 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1 Gear Grease EP 1		
---	--	--

Check every 50 hours

COOLING SYSTEM

Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Coolant SP 15+	PRODUCT RECOMMENDATION 2 Coolant SP 12	PRODUCT RECOMMENDATION 3 Coolant -38 Organic NF
---	--	---

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.