

MCCORMICK MTX MTX125 (2001-2002)

ENGINE 1006.60T
Capacity: 11,6 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 20W-50

Check every 10 hours, change every 300 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Armado Synth 5W-30

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT MFD
Capacity: 6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 300 hours, change every 1200 hours

DIFFERENTIAL FRONT INDEPENDENT FRONT SUSPENSION
Capacity: 2,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 300 hours, change every 1200 hours

HUB REDUCTIONS FRONT Independent Front Suspension
Capacity: 1,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 300 hours, change every 1200 hours

MCCORMICK MTX MTX125 (2001-2002)**HUB REDUCTIONS FRONT MFD**

Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Check every 300 hours, change every 1200 hours***POWER TAKE OFF FRONT**

Capacity: 2,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Abacot MEP 220***Check every 10 hours, change every 300 hours***TRANSMISSION/HYDRAULIC SYSTEM 16/12**

Capacity: 75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus***Check every 10 hours, change every 1200 hours***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 50 hours***COOLING SYSTEM**

Capacity: 19,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2400 hours*

MCCORMICK MTX MTX125 (2001-2002)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.