

MCCORMICK MTX MTX135 TIER3 (2003-2007)



MOTOR BetaPower 24V
Kapacitet: 16 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SHPD 10W-40		

Kontroller alle 10 timer, skift alle 500 timer

DIFFERENTIALE BEGRÆNSET SLIP FOR UAFHÆNGIG FRONTOPHÆNGNING
Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 250 timer, skift alle 500 timer

DIFFERENTIALE FOR MFD
Kapacitet: 6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 500 timer

MCCORMICK MTX MTX135 TIER3 (2003-2007)



DIFFERENTIALE FOR UAFHÆNGIG AFFJEDRING FOR

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 500 timer

GEAR/HYDRAULISK SYSTEM

Kapacitet: 75 liter, Kapacitet: 12 liter (ekstra kapacitet)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1000 timer

HJULNAVSREDUKTION FORAN MED BREMSER

Kapacitet: 2 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 500 timer

KRAFTOVERFØRING FOR

Kapacitet: 2,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 220

Kontroller alle 10 timer, skift alle 250 timer

NAVREDUKTIONER FOR UDEN BREMSER

Kapacitet: 0,6 liter (MFD), Kapacitet: 1,5 liter (Uafhængig foraksel)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 500 timer

MCCORMICK MTX MTX135 TIER3 (2003-2007)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 26,5 liter, Kapacitet: 28,5 liter (+ kabine)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.