

MCCORMICK MTX MTX140 (2001-2002)

ENGINE 1006.60T
Capacity: 11,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50

Check every 10 hours, change every 300 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Armado Synth 5W-30

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT MFD
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 300 hours, change every 1200 hours

DIFFERENTIAL FRONT INDEPENDENT FRONT SUSPENSION
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 300 hours, change every 1200 hours

HUB REDUCTIONS FRONT Independent Front Suspension
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 300 hours, change every 1200 hours

MCCORMICK MTX MTX140 (2001-2002)**HUB REDUCTIONS FRONT MFD**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Check every 300 hours, change every 1200 hours***POWER TAKE OFF FRONT**

Capacity: 2,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Abacot MEP 220***Check every 10 hours, change every 300 hours***TRANSMISSION/HYDRAULIC SYSTEM 16/12**

Capacity: 75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus***Check every 10 hours, change every 1200 hours***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 50 hours***COOLING SYSTEM**

Capacity: 18 liter, Capacity: 20 liter (+ cabin)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2400 hours*

MCCORMICK MTX MTX140 (2001-2002)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.