

MCCORMICK XTX XTX215 TIER2 (2005-2009)



MOTOR Cummins QSB
Kapacitet: 15 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SHPD 10W-40		

Kontroller alle 10 timer, skift alle 500 timer

DIFFERENTIALE FOR (4x4)
Kapacitet: 6 liter (MFD), Kapacitet: 2,2 liter (Uafhængig foraksel)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 250 timer

KRAFTOVERFØRING FOR
Kapacitet: 2,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 10 timer, skift alle 500 timer

MCCORMICK XTX XTX215 TIER2 (2005-2009)



NAVREDUKTIONER FOR (4x4)

Kapacitet: 2 liter (+ forbremses), Kapacitet: 1,5 liter (Uden bremses)

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND		KLIMA
Første Service		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 250 timer

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 95 liter, Kapacitet: 12 liter (Hjælpehydraulik)

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1000 timer

KØLESYSTEM

Kapacitet: 21 liter

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.