

MERCEDES-BENZ MB TRAC MB TRAC 800

(440) (1982-1987)

**ENGINE** OM314

Capacity: 9 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 200 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 200 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Change every 200 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 200 hours*

USE	CLIMATE
Severe	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 100 hours*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 100 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Change every 100 hours*

MERCEDES-BENZ MB TRAC MB TRAC 800

(440) (1982-1987)



USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Change every 100 hours</i>		

DIFFERENTIAL LOCK AIR OPERATED		
Capacity: 0,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HDX 10W		
<i>Check every 200 hours, change every 400 hours</i>		

DIFFERENTIAL FRONT		
Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 1 months, change every 800 hours/ 12 months</i>		

DIFFERENTIAL REAR		
Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 1 months, change every 800 hours/ 12 months</i>		

HUB REDUCTIONS FRONT AL 7		
Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 200 hours, change every 400 hours</i>		



MERCEDES-BENZ MB TRAC MB TRAC 800 (440) (1982-1987)


HUB REDUCTIONS REAR HL 7/07 DL-11,5 (L/LS)

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 200 hours, change every 400 hours

POWER TAKE OFF FRONT

Capacity: 5,75 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		

Check every 1 months, change every 800 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W		

Check every 1 months, change every 800 hours/ 12 months

TRANSMISSION MANUAL 16/8

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W	Gearlube GL-4 80W-90	

Check every 1 months, change every 800 hours/ 12 months

MERCEDES-BENZ MB TRAC MB TRAC 800 (440) (1982-1987)



HYDRAULIC SYSTEM

Capacity: 30 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 200 hours, change every 800 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	Perlus H 32	

Check every 200 hours, change every 800 hours/ 12 months

HYDRAULIC SYSTEM DIFFERENTIAL LOCK

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 10W	ATF-A	

Check every 200 hours, change every 400 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 12 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Check every 1 months, change every 12 months

MERCEDES-BENZ MB TRAC MB TRAC 800 (440) (1982-1987)



POWER STEERING

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 1 months, change every 1600 hours/ 24 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 1 months, change every 1600 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 400 hours

COOLING SYSTEM

Capacity: 16,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.