

**NEW HOLLAND VL/VM VM460 (2004-2006)**

**ENGINE** Iveco/Aifo  
Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Armado Synth 5W-30</b>

*Check every 10 hours, change every 400 hours/ 12 months*

**HYDRAULIC SYSTEM HYDROSTATIC DRIVE**  
Capacity: 65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 68</b>	<b>Perlus AF 68</b>	

*Check every 10 hours, change every 800 hours/ 24 months*

**GREASE POINTS/NIPPLES NON FOOD PARTS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

*Change every 50 hours*

**GREASE POINTS/NIPPLES SHAKING CONTROL ECU**  
Capacity: 1 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

**COOLING SYSTEM**  
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 10 hours, change every 800 hours/ 24 months*

# NEW HOLLAND VL/VM VM460 (2004-2006)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*