

# NEW HOLLAND T4000 T4040 DELUXE SUPERSTEER (2008-2011)

**ENGINE** NEF Tier 3

Capacity: 9,5 liter, Filter capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

**DIFFERENTIAL FRONT**

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

**HUB REDUCTIONS FRONT**

Capacity: 0,5 liter (+ front brakes), Capacity: 1 liter (Without brakes)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

**POWER TAKE OFF FRONT**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

**TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 44 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

# NEW HOLLAND T4000 T4040 DELUXE SUPERSTEER (2008-2011)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter, Capacity: 1 liter (+ front brakes)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>LHM +</b>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

## COOLING SYSTEM

Capacity: 14 liter, Capacity: 16 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.