## **NEW HOLLAND T7500 T7540** (2007-2010)



ENGINE CR Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Armado Synth 5W-30

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT Capacity: 2,2 liter (20.25 suspension), Capacity	apacity: 5,5 liter (20.29 suspension), Capacit	ty: 8 liter (Standard)
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140
Chock avany 250 hours, change avany 1	200 hours/12 months	

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT + BR Capacity: 2 liter	AKES		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Charles aver 250 hours above a	10001 / 10 / 1		

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT WITHO Capacity: 1,5 liter	OUT BRAKES	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140
Check every 250 hours, change eve	ry 1000 hours/ 12 months	·

HUB REDUCTIONS REAR
Capacity: 12 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

Capacity: 12 liter

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 2

Gearlube GL-5 85W-140

## **NEW HOLLAND T7500 T7540** (2007-2010)



POWER TAKE OFF FRONT Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM AutoCommand Capacity: 60 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak CVT 10W-40	
01 1 0501 1 10001 110	<u> </u>

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM + POWER S Capacity: 52 liter	STEERING	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		
Check every 250 hours, change every 200	0 hours/ 24 months	

COOLING SYSTEM Capacity: 25 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

## PRODUCT RECOMMENDATION

## **NEW HOLLAND T7500 T7540** (2007-2010)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.