

NEW HOLLAND T8 T8.275 TIER 4A ZDRC06500-> (2012-2015)



MOTOR FPT Cursor 9
Kapacitet: 25 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,5 %	Middelhavsagtigt

PRODUKTANBEFALING 1		
Agridiesel CRD+ 15W-40		

Kontroller alle 10 timer, skift alle 600 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,5 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Kontroller alle 10 timer, skift alle 600 timer

DIFFERENTIALE FOR

Kapacitet: 11,8 liter (Aksel, standard og høj belastning), Kapacitet: 17,5 liter (Klasse 4,75 aksel, med suspension), Kapacitet: 15 liter (Klasse 5 aksel), Kapacitet: 17,5 liter (Klasse 5 aksel, med suspension)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 300 timer, skift alle 1200 timer/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 300 timer, skift alle 1200 timer/ 12 måneder

KRAFTOVERFØRING FOR

Kapacitet: 4,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Kontroller alle 300 timer, skift alle 600 timer

NEW HOLLAND T8 T8.275 TIER 4A ZDRC06500-> (2012-2015)



NAVREDUKTIONER FOR

Kapacitet: 3,3 liter (Heavy Duty), Kapacitet: 4,3 liter (Klasse 4,75 aksel, med suspension), Kapacitet: 6 liter (Klasse 5 aksel), Kapacitet: 4,5 liter (Klasse 5 aksel, med suspension), Kapacitet: 1,4 liter (Standard)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 300 timer, skift alle 1200 timer/ 12 måneder

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 300 timer, skift alle 1200 timer/ 12 måneder

TRANSAXEL/HYDRAULISK SYSTEM

Kapacitet: 206 liter (AutoCommand, høj belastning), Kapacitet: 187 liter (AutoCommand, standard), Kapacitet: 172 liter (Gearskit)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Kontroller alle 10 timer, skift alle 1500 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 26,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 10 timer, skift alle 2000 timer

NEW HOLLAND T8 T8.275 TIER 4A ZDRC06500-> (2012-2015)



DIESELUDSTØDNINGSVÆSKE

Kapacitet: 87 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.