

# NEW HOLLAND T8 T8.275 TIER 4A

## ZDRC06500-> (2012-2015)



**ENGINE** FPT Cursor 9  
Capacity: 25 liter

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

*Check every 10 hours, change every 600 hours*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra 10W-40**

PRODUCT RECOMMENDATION 2

**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 3

**Agrisynth MSP 10W-40**

*Check every 10 hours, change every 600 hours*

### DIFFERENTIAL FRONT

Capacity: 17,5 liter (Class 4.75 axle with suspension), Capacity: 15 liter (Class 5 axle), Capacity: 17,5 liter (Class 5 axle with suspension), Capacity: 11,8 liter (Standard and Heavy Duty axle)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140**

*Check every 300 hours, change every 1200 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 300 hours, change every 1200 hours/ 12 months*

# NEW HOLLAND T8 T8.275 TIER 4A

## ZDRC06500-> (2012-2015)



### HUB REDUCTIONS FRONT

Capacity: 4,3 liter (Class 4.75 axle with suspension), Capacity: 6 liter (Class 5 axle), Capacity: 4,5 liter (Class 5 axle with suspension), Capacity: 3,3 liter (Heavy Duty), Capacity: 1,4 liter (Standard)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

Check every 300 hours, change every 1200 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Check every 300 hours, change every 1200 hours/ 12 months

### POWER TAKE OFF FRONT

Capacity: 4,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>

Check every 300 hours, change every 600 hours

### TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 206 liter (AutoCommand, heavy duty), Capacity: 187 liter (AutoCommand, standard), Capacity: 172 liter (Powershift)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>

Check every 10 hours, change every 1500 hours

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

Change every 50 hours

# NEW HOLLAND T8 T8.275 TIER 4A

## ZDRC06500-> (2012-2015)



### COOLING SYSTEM

Capacity: 26,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Check every 10 hours, change every 2000 hours

### DIESEL EXHAUST FLUID

Capacity: 87 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*