

NEW HOLLAND T8000 T8020 (2007-2011)**ENGINE Tier III**

Capacity: 21 liter, Filter capacity: 2 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 300 hours

| USE | | CLIMATE |
|---------------------------|-------------------------------------|---------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Armado Synth 5W-30 | Dieselfleet LSP Ultra 10W-30 | |

*Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT WITH 10 BOLTS**

Capacity: 12,3 liter (Standard), Capacity: 13,25 liter (Supersteer)

| USE | | CLIMATE |
|--------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

*Check every 300 hours, change every 1200 hours/ 12 months***DIFFERENTIAL FRONT WITH 12 BOLTS**

Capacity: 11,8 liter (Standard), Capacity: 13,25 liter (Supersteer)

| USE | | CLIMATE |
|--------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

*Check every 300 hours, change every 1200 hours/ 12 months***HUB REDUCTIONS FRONT WITH 10 BOLTS**

Capacity: 1,4 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 300 hours, change every 1200 hours/ 12 months

NEW HOLLAND T8000 T8020 (2007-2011)**HUB REDUCTIONS FRONT WITH 12 BOLTS**

Capacity: 3,3 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

*Check every 300 hours, change every 1200 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 172 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |

*Check every 10 hours, change every 1500 hours***GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|---------------------------------|------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

*Change every 50 hours***COOLING SYSTEM**

Capacity: 26,5 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Check every 10 hours, change every 2100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.