## **NEW HOLLAND TD-D TD 90D** (2004-2008)



ENGINE Capacity: 11,7 liter, Filter capacity: 0,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Dieselfleet LSP Ultra 10W-30	

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 300 hours, change every 1200 hours/24 months		

HUB REDUCTIONS FRONT
Capacity: 1,25 liter

USE

Normal

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Check every 300 hours, change every 1200 hours/24 months

Capacity: 1,25 liter

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 2

Agrifluid HT

Check every 300 hours, change every 1200 hours/24 months

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 12/12 Capacity: 55 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Check every 300 hours, change ev	ery 1200 hours/ 24 months		

HYDROSTATIC STEERING Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 10 hours, change eve	ry 1200 hours	'

## **NEW HOLLAND TD-D TD 90D** (2004-2008)



HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	
Check every 10 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 50 hours		

COOLING SYSTEM Capacity: 14 liter, Capacity: 16 liter (+ cabin)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Charles your ED hours phones over 1200 hours (24 months			

Check every 50 hours, change every 1200 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.