NEW HOLLAND TM TM 150 (2000-2002)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Asyntho 5W-30

Check every 10 hours, change every 300 hours

Check every 300 hours, change every 1200 hours/ 12 months

DIFFERENTIAL FRONT Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 300 hours, change ev	rery 1200 hours/ 12 months	·

HUB REDUCTIONS FRONT
Capacity: 2,15 liter

USE
Normal

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

CLIMATE
Moderate

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

Kroontrak MTH 10W-30

Agrifluid HT

TRANSAXLE/HYDRAULIC SYSTE Capacity: 100 liter	PowerCommand 17/6	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 300 hours, change every	ery 1200 hours/ 12 months	

TRANSAXLE/HYDRAULIC SYSTEM Range Command 17/6 Capacity: 90 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Check every 300 hours, change ev	rery 1200 hours/ 12 months	<u> </u>	

NEW HOLLAND TM TM 150 (2000-2002)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 50 hours	'	

COOLING SYSTEM Capacity: 23,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

Check every 10 hours, change every 1200 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.