

NEW HOLLAND VL/VM VL610 (2004-2006)



MOTOR Iveco/Aifo Kapacitet: 16 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Agridiesel MSP 15W-40	PRODUKTANBEFALING 2 Agridiesel CRD+ 15W-40	PRODUKTANBEFALING 3 Armado Synth 5W-30
<i>Kontroller alle 10 timer, skift alle 400 timer/ 12 måneder</i>		

HYDRAULISK SYSTEM HYDROSTATISK DREV Kapacitet: 65 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Perlus H 68	PRODUKTANBEFALING 2 Perlus AF 68	
<i>Kontroller alle 10 timer, skift alle 800 timer/ 24 måneder</i>		

SMØREPUNKTER/NIPLER NON FOOD-DELE		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 2 MP Lithep Grease EP 2	
<i>Skift alle 50 timer</i>		

SMØREPUNKTER/NIPLER RYSTESTYRINGS-ECU Kapacitet: 1 kg		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 MoS2 Grease EP 2		

KØLESYSTEM Kapacitet: 20 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	
<i>Kontroller alle 10 timer, skift alle 800 timer/ 24 måneder</i>		

NEW HOLLAND VL/VM VL610 (2004-2006)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.