

RASANT KOMBI TRAK KOMBI TRAK 1503 S

(1988 AND AFTER)

**ENGINE**

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Multifleet SHPD 15W-40***Check every 10 hours, change every 100 hours***DIFFERENTIAL FRONT**

Capacity: 1,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 8 hours, change every 500 hours***REDUCTION UNITS REAR**

Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 8 hours, change every 500 hours***TRANSAXLE MANUAL**

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 32****PRODUCT RECOMMENDATION 2****Perlus AF 32***Check every 8 hours, change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 10 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 32****PRODUCT RECOMMENDATION 2****Perlus AF 32***Check every 8 hours, change every 500 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

RASANT KOMBI TRAK KOMBI TRAK 1503 S **(1988 AND AFTER)**



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.