## RASANT KOMBI TRAK RS2805T (2000 AND AFTER)



<b>ENGINE</b> V3300TE Capacity: 13,5 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 250 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		

Change every 35 hours

DIFFERENTIAL FRONT Capacity: 2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
01 1 1001 1 500	

Check every 100 hours, change every 500 hours/24 months

HUB REDUCTIONS REAR Capacity: 1,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Gearlube GL-5 80W-90	

Check every 100 hours, change every 1000 hours/24 months

POWER TAKE OFF FRONT Capacity: 2,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Check every 50 hours

## RASANT KOMBI TRAK RS2805T (2000 AND AFTER)



TRANSFERBOX Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	

Check every 100 hours, change every 500 hours/24 months

TRANSMISSION Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Check avery 100 hours, change avery 500 hours/ 12 months		

Check every 100 hours, change every 500 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	

Check every 100 hours, change every 500 hours/24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	

Change every 35 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		

## RASANT KOMBI TRAK RS2805T (2000 AND AFTER)



COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.