PRODUCT RECOMMENDATION

REFORM MULI MULI 560 (1992 AND AFTER)

ENGINE Kubota
Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SHPD 10W-40**	

Check every 10 hours, change every 200 hours/ 12 months

DIFFERENTIAL REAR
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 200 hours, change every 600 hours/ 24 months

POWER TAKE OFF FRONT
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 200 hours

REDUCTION UNITS REAR
Capacity: 0,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 200 hours, change every 600 hours/ 24 months

TRANSAXLE MANUAL
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**SP Gear 5015**	**Gearlube GL-4 80W**

Check every 200 hours, change every 600 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

REFORM MULI MULI 560 (1992 AND AFTER)

HYDRAULIC SYSTEM
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus AF 46**	

Check every 100 hours, change every 600 hours/ 24 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 100 hours, change every 24 months

HYDRAULIC CLUTCH SYSTEM
Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 100 hours, change every 24 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 100 hours

COOLING SYSTEM
Capacity: 12 liter, Capacity: 13 liter (+ heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

REFORM MULI MULI 560 (1992 AND AFTER)

information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367