

## ENGINE MWM D 327-2

# Capacity: 6,3 liter, Filter capacity: 0,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# TRANSAXLE/HYDRAULIC SYSTEM 10/2

#### Capacity: 26,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES OTHERS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			
Chaolic avery 200 hours	· · ·	· · ·		

Check every 200 hours

## **BELT PULLEY** Capacity: 0,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

STEERING BOX Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Charles ware 200 hours		

Check every 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.