RENAULT CERES CERES 340 (X) 2WD/4WD (1998-2001)



Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
ENGINE DPS 4039 TRT Capacity: 11 liter		

Check every 10 hours, change every 200 hours

DIFFERENTIAL FRONT (4x4) Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
	-

Check every 200 hours, change every 800 hours/ 12 months

CLIMATE
Moderate

Check every 200 hours, change every 800 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 200	hours	

TRANSAXLE/HYDRAULIC SYSTEM 10/8 Capacity: 60 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 10 hours, change every 800 hours/ 12 months		

RENAULT CERES CERES 340 (X) 2WD/4WD (1998-2001)



HYDRAULIC BRAKE SYSTEM
Capacity: 0,9 liter

USE

Normal

PRODUCT RECOMMENDATION 2

Drauliquid DOT 5.1

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Drauliquid-LV Super DOT 4

Drauliquid-S DOT 4

Check every 600 hours, change every 800 hours/ 12 months

GREASE POINTS/NIPPLES 3-POINT HITCH		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 50 hours		

GREASE POINTS/NIPPLES OTHERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 200 hours		

COOLING SYSTEM Capacity: 13,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	
Check every 10 hours, change every 1200 hours/24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.