

# RENAULT CERES CERES 65 4WD (1993-1998)

**ENGINE** MWM D 226-3

Capacity: 7,75 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 200 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT***Check every 100 hours, change every 800 hours***HUB REDUCTIONS FRONT (4x4)**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT***Check every 50 hours, change every 800 hours***TRANSAXLE/HYDRAULIC SYSTEM 10/10**

Capacity: 54 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT***Check every 200 hours, change every 800 hours/ 12 months***GREASE POINTS/NIPPLES 3-POINT HITCH**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 2

**MP Lithep Grease EP 2***Check every 50 hours*

# RENAULT CERES CERES 65 4WD (1993-1998)



## GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

Check every 100 hours

## GREASE POINTS/NIPPLES FRONT SUSPENSION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

Check every 100 hours

## COOLING SYSTEM

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 16</b>		

Change every 600 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.