## **RENAULT ARES ARES 546 (H5312)** (2003-2008)



ENGINE 4045 TRT53 Capacity: 12,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 300 hours		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

**Multifleet SHPD 15W-40** 

Change every 100 hours

Agridiesel CRD+ 15W-40

<b>DIFFERENTIAL FRONT</b> A 88-1 Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 300 hours, change every 1200 hours/ 12 months

<b>DIFFERENTIAL FRONT</b> ProActiv 2043 SI Capacity: 5,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Charle over 200 hours change over 1200 hours / 12 months		

Check every 300 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT PA 721 Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 300 hours, change every 600 hours/ 12 months	

## **RENAULT ARES ARES 546 (H5312)** (2003-2008)



POWER TAKE OFF FRONT Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 50 hours, change every 600 hours

TRANSMISSION/HYDRAULIC SYSTEM Capacity: 65 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		
Check every 10 hours, change every 1200 hours/ 12 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 50 hours

COOLING SYSTEM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		
Check every 10 hours, change every 1500 hours/ 24 months		

## PRODUCT RECOMMENDATION

## **RENAULT ARES ARES 546 (H5312)** (2003-2008)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.