RENAULT ARES ARES 696 (H8242) (2003-2008)



ENGINE 6068 TRT55 Capacity: 17 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 300 kg	hours	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Multifleet SHPD 15W-40

Change every 100 hours

Agridiesel CRD+ 15W-40

DIFFERENTIAL FRONT A 88-1 Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 300 hours, change every 1200 hours/ 12 months

DIFFERENTIAL FRONT ProActiv 2043 SI Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 300 hours, change every 1200 hours/ 12	months

HUB REDUCTIONS FRONT PA 721 Capacity: 1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Chack avery 200 hours, change avery 600 hours/12 month	

Check every 300 hours, change every 600 hours/ 12 months

RENAULT ARES ARES 696 (H8242) (2003-2008)



POWER TAKE OFF FRONT Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
01 1 501 1 0001	

Check every 50 hours, change every 600 hours

TRANSMISSION/HYDRAULIC SYSTEM Capacity: 65 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		
Check every 10 hours, change every 12) hours/ 12 months	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 50 hours

COOLING SYSTEM Capacity: 22 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 16			
Check every 10 hours, change ever	1500 hours/ 24 months	,	

PRODUCT RECOMMENDATION

RENAULT ARES ARES 696 (H8242) (2003-2008)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.