

RENAULT TA, TE, TL, TS, TX, TZ 175-74 TZ (1990-1992)



MOTOR MWM D 226-B6
Kapacitet: 20,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE FOR (4x4)
Kapacitet: 4,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 100 timer, skift alle 800 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Skift alle 100 timer

NAVREDUKTIONER FOR (4x4)
Kapacitet: 1,35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 50 timer, skift alle 800 timer/ 12 måneder

TRANSAKSEL/HYDRAULISK SYSTEM 24/8
Kapacitet: 60 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 10 timer, skift alle 800 timer/ 12 måneder

RENAULT TA, TE, TL, TS, TX, TZ 175-74 TZ (1990-1992)



HYDRAULISK BREMSESISTEM

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 600 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 50 timer

SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 200 timer

KØLESYSTEM

Kapacitet: 24,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 16

Kontroller alle 10 timer, skift alle 600 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.