

RENAULT TA, TE, TL, TS, TX, TZ 75-34 TX (1988-1994)



MOTOR MWM D 226-4
Kapacitet: 11,25 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE FOR (4x4)

Kapacitet: 3,55 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 100 timer, skift alle 800 timer

NAVREDUKTIONER FOR (4x4)

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 800 timer

TRANSAKSEL/HYDRAULISK SYSTEM 12/12

Kapacitet: 48 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 10 timer, skift alle 800 timer/ 12 måneder

TRANSAKSEL/HYDRAULISK SYSTEM 24/24

Kapacitet: 52 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 10 timer, skift alle 800 timer/ 12 måneder

RENAULT TA, TE, TL, TS, TX, TZ 75-34 TX (1988-1994)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 600 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 12,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 16

Skift alle 600 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.