

# RENAULT TA, TE, TL, TS, TX, TZ 80-14 TX (1984-1989)



**MOTOR** MWM D 226-4  
Kapacitet: 11,3 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

*Kontroller alle 10 timer, skift alle 100 timer*

**DIFFERENTIALE FOR** (4x4)  
Kapacitet: 3,55 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**KRAFTOVERFØRING FOR**  
Kapacitet: 0,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**NAVREDUKTIONER FOR** (4x4)  
Kapacitet: 0,9 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**TRANSAKSEL/HYDRAULISK SYSTEM**  
Kapacitet: 58 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**HYDRAULISK BREMSESYSTEM**  
Kapacitet: 0,9 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

PRODUKTANBEFALING 3

**Drauliquid DOT 3**

*Skift alle 600 timer/ 12 måneder*

**SMØREPUNKTER/NIPLER ANDRE**

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 2

**MP Lithep Grease EP 2**

*Kontroller alle 50 timer*

# RENAULT TA, TE, TL, TS, TX, TZ 80-14 TX (1984-1989)



## KØLESYSTEM

Kapacitet: 13,5 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 16**

*Skift alle 600 timer/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*