

# RENAULT TA, TE, TL, TS, TX, TZ 120-14 TX-TS '16' (1987-1989)



**ENGINE** MWM D 226-6  
Capacity: 14,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## DIFFERENTIAL FRONT (4x4)

Capacity: 4,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 100 hours, change every 1200 hours*

## HUB REDUCTIONS FRONT (4x4)

Capacity: 1,35 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 1200 hours*

## POWER TAKE OFF FRONT

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Change every 100 hours*

## TRANSAXLE/HYDRAULIC SYSTEM 16/16

Capacity: 58 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 10 hours, change every 1200 hours/ 12 months*

# RENAULT TA, TE, TL, TS, TX, TZ 120-14 TX-TS '16' (1987-1989)



## HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Change every 600 hours

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 50 hours

## COOLING SYSTEM

Capacity: 13 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 16</b>     |  |          |

Change every 600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.