

PRODUCT RECOMMENDATION

# RENAULT TA, TE, TL, TS, TX, TZ 133-54 TX, TS, TA, TZ (1989-1994)



**ENGINE** MWM D 226-6

Capacity: 14,75 liter, Filter capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL FRONT (4x4)**

Capacity: 4,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 100 hours, change every 800 hours*

**HUB REDUCTIONS FRONT (4x4)**

Capacity: 1,35 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 50 hours, change every 800 hours*

**POWER TAKE OFF FRONT**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 10 hours, change every 100 hours*

**TRANSAXLE/HYDRAULIC SYSTEM 24/8**

Capacity: 60 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 10 hours, change every 800 hours/ 12 months*

PRODUCT RECOMMENDATION

# RENAULT TA, TE, TL, TS, TX, TZ 133-54 TX, TS, TA, TZ (1989-1994)



## HYDRAULIC BRAKE SYSTEM

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

*Change every 600 hours/ 12 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

*Check every 50 hours*

## COOLING SYSTEM

Capacity: 23 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 16**

*Change every 600 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*