RENAULT TA, TE, TL, TS, TX, TZ 155-54 TZ (1989-1993)



ENGINE MWM D 226-B6 Capacity: 15,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 100 hours		

DIFFERENTIAL FRONT (4x4) Capacity: 4,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 100 hours, change every 8	00 hours/ 12 months	

HUB REDUCTIONS FRONT (4x4) Capacity: 1,35 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 800 hours/ 12 months		

POWER TAKE OFF FRONT Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 100 hours	

TRANSAXLE/HYDRAULIC SYSTEM 24/8 Capacity: 60 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 10 hours, change every 800 hours/ 12 months		

RENAULT TA, TE, TL, TS, TX, TZ 155-54 TZ (1989-1993)



HYDRAULIC BRAKE SYSTEM
Capacity: 1 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 600 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours	,	,

COOLING SYSTEM Capacity: 24,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	

Check every 10 hours, change every 600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.