

SAME ANCIENT MODELS LEOPARD 85

(1978-1984)



ENGINE Same DA1054P
Capacity: 13,3 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1 Multifleet SCD 40	PRODUCT RECOMMENDATION 2 HDX 40	
--	---	--

Check every 10 hours, change every 125 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1 HDX 30		
---	--	--

Check every 10 hours, change every 125 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40		
---	--	--

Check every 10 hours, change every 125 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1 HDX 20W-20		
---	--	--

Check every 10 hours, change every 125 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40		
---	--	--

Check every 10 hours, change every 125 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Agrifluid HT		
---	--	--

Check every 125 hours, change every 1000 hours

SAME ANCIENT MODELS LEOPARD 85 (1978-1984)



HUB REDUCTIONS FRONT (4x4)

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 125 hours, change every 1000 hours*

TRANSAXLE MANUAL 24/6

Capacity: 72,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 125 hours, change every 3000 hours*

HYDRAULIC SYSTEM

Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 125 hours, change every 3000 hours*

POWER STEERING

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 125 hours, change every 1000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 20 hours*

SAME ANCIENT MODELS LEOPARD 85

(1978-1984)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.