## **SAME DORADO DORADO 76** (2004-2006)



PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40** 

<b>ENGINE</b> Perkins 1000.4-W Capacity: 12 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 300	hours/ 12 months	
USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Change every 50 hours

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 10 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 10 hours, change every 1200 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 41 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 10 hours, change every	1200 hours/ 12 months	

## **SAME DORADO DORADO 76** (2004-2006)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 24 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	1	

COOLING SYSTEM Capacity: 11 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1	Midderate
Coolant -38 Organic NF	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo

Check every 10 hours, change every 1200 hours/ 12 months