

SAME DORADO DORADO S 100 (24"/28") - >9001 (2008 AND AFTER)

**ENGINE** 1000.4-WT 5E

Capacity: 12 liter, Filter capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 300 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

*Change every 50 hours***DIFFERENTIAL FRONT**

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

*Check every 10 hours, change every 1200 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 1,5 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

*Check every 10 hours, change every 1200 hours/ 12 months***POWER TAKE OFF FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 10 hours, change every 1200 hours/ 12 months

SAME DORADO DORADO S 100 (24"/28") - >9001 (2008 AND AFTER)



TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 41 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 10 hours, change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.